

**Subpart AG—Kaolin Subcategory
[Reserved]**

**Subpart AH—Ball Clay
Subcategory [Reserved]**

**Subpart AI—Feldspar Subcategory
[Reserved]**

**Subpart AJ—Talc, Steatite, Soap-
stone and Pyrophyllite Sub-
category [Reserved]**

**Subpart AK—Garnet Subcategory
[Reserved]**

**Subpart AL—Graphite
Subcategory**

**§ 436.380 Applicability; description of
the graphite subcategory.**

The provisions of this subpart are applicable to the mining and processing of naturally occurring graphite.

§ 436.381 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term “mine drainage” shall mean any water drained, pumped or siphoned from a mine.

**§ 436.382 Effluent limitations guide-
lines representing the degree of ef-
fluent reduction attainable by the
application of the best practicable
control technology currently avail-
able.**

(a) Except as provided in §§125.30 through 125.32, and subject to the provisions of paragraph (b) of this section, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
TSS	20 mg/l	10 mg/l.
Total Fe	2 mg/l	1 mg/l.
pH	(¹)	(¹)

¹ Within the range 6.0 to 9.0.

(b) Only that volume of water resulting from precipitation that exceeds the maximum safe surge capacity of a process waste water impoundment may be discharged from that impoundment. The height difference between the maximum safe surge capacity level and the normal operating level must be greater than the inches of rain representing the 10-year, 24-hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the locality in which such impoundment is located.

[40 FR 48657, Oct. 16, 1975, as amended at 60 FR 33969, June 29, 1995; 60 FR 35796, July 11, 1995]

**PART 439—PHARMACEUTICAL
MANUFACTURING POINT
SOURCE CATEGORY**

GENERAL

Sec.

- 439.0 Applicability.
- 439.1 General definitions.
- 439.2 Monitoring requirements.
- 439.3 General pretreatment standards.
- 439.4 Monitoring requirements.

**Subpart A—Fermentation Products
Subcategory**

- 439.10 Applicability.
- 439.11 Specialized definitions.
- 439.12 Effluent limitations attainable by the application of the best practicable control technology currently available (BPT).
- 439.13 Effluent limitations attainable by the application of the best conventional pollutant control technology (BCT).
- 439.14 Effluent limitations attainable by the application of best available technology economically achievable (BAT).
- 439.15 Standards of performance for new (point) sources (NSPS).
- 439.16 Pretreatment standards for existing sources (PSES).
- 439.17 Pretreatment standards for new sources (PSNS).